9CH,RX VCO TUNING IS 2.0V
BAND1_UK_Fre
BAND1:시 UK_Fre에 연결port로 control함.
UK:LOW CE:HIGH
VOL_OUT
POP_MUTE
MIC_IN
SW_ON
VLB_SW
VLB_B+
AM_FM
VLB_IF_IN
VLB_RF_IN
VLB_PD
VLB_FIN
PLL_DATA
SQLB
SQL
LEVEL SQ: NOT USE
ASQ:HIGH
FM:HIGH
SIGNAL YES: LOW SIGNAL NO:HIGH
VLB OFF: LOW
VLB ON: HIGH
MAX.1.85KHZ
MAX.82% AT CE
LSQ_IN
MODULE1
NU
RX_TONE_INTONE_DET_OUT
TONE_EN
TONE_TX_OUT
GND
5V
TONE_CLK
DATA
STB
XIN
J5
VOLSQ BOARD SOLDER
J4
MAIN BOARD SOLDER
J6
VOL_BOARD_SOLDER
J3
VLB BOARD
J1
SQ_MIC GAN
U1
TDA2003
IC1
LC7152NM
IC2
KIA78L05F
IC4
MC3361D/UTC3361
XT1
12.8MHz
XT2
10.245MHZ
CF1
CFW455HT
ANT1
CH-239
JP1
ANTENNA LUG
L1
0.45*2.3*6.5T(R) With M52 BEAD+22220001
L2
0.55*3.4*6.5T(R)
L3
0.55*3.4*7.5T(R)
L4
0.55*3.4*7.5T(R)
L5
0.55*3.4*9.5T(R)
L9
19mm_Trans
J2
CON1_19
13.8V
Title
EXCALIBUR_13.8V_MAIN
Size
A1
Document Number
CE MULTI VERSION
Rev
PP
Date:
Wednesday, September 09, 2009
Sheet
1
of
1